



SPECS

FRAME	
SIZES	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
COLORS	Knight Shield, Phantom Green
FRAME	ALUXX-Grade Aluminum, disc
FORK	SR Suntour XCM30, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm travel (29) L: 780mm (27.5) / 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm travel (29) L: 70mm (27.5) / 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (27.5) / 375mm (29) XL: 375mm (29) XXL: 375mm (29)
SADDLE	Giant custom
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT SL-M9295, 1x9
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	microSHIFT Advent M6195M
BRAKES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro HDC M275
CASSETTE	microSHIFT CS-H093, 11x46
CHAIN	KMC X9
CRANKSET	ProWheel Charm, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	cartridge
WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	alloy, sealed bearing
SPOKES	stainless, 14g
TIRES	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tire size

FEATURES

- Frame: ALUXX-Grade Aluminum, disc
- Fork: SR Suntour XCM30, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
- Shifters: microSHIFT SL-M9295, 1x9
- Crankset: ProWheel Charm, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175mm travel (29) L: 175mm (27.5) / 175mm (29) XL: 175mm (29) XXL: 175mm (29)
- Colors: Knight Shield, Phantom Green

Recommended Retail Price: \$750

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")	XL (29")
Seat Tube Length (inch)	13.8	15.2	15.4	16.9	17.3	19.3	21.1
Seat Tube Angle	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Top Tube Length (inch)	21.4	22.4	22.7	23.5	23.6	24.4	25.2
Head Tube Length (inch)	3.7	4.5	3.7	5.1	4.1	4.9	5.5
Head Tube Angle	67.5°	67.5°	68.5°	67.5°	68.5°	68.5°	68.5°
Fork Rake (inch)	1.7	1.7	2	1.7	2	2	2
Trail (inch)	4.1	4.1	3.7	4.1	3.7	3.7	3.7
Wheelbase (inch)	42.5	43.5	44.3	44.8	45.3	46.1	46.9
Chain Stay Length (inch)	17.3	17.3	17.9	17.3	17.9	17.9	17.9
Bottom Bracket Drop (inch)	1.8	1.8	2.2	1.8	2.2	2.2	2.2
Stack (inch)	21	22.5	23.7	23.5	24.1	24.8	25.4
Reach (inch)	15.2	15.9	15.9	16.7	16.7	17.3	17.9
Stand Over Height (inch)	27	28	28.8	29.4	30.2	31.7	33
Handlebar Width (inch)	30.7	30.7	30.7	30.7	30.7	30.7	30.7
Stem Length (inch)	1.6	2	2	2.4	2.4	2.8	3.1
Crank Length (inch)	6.5	6.7	6.7	6.9	6.9	6.9	6.9
Wheel Size	27.5"	27.5"	29"	27.5"	29"	29"	29"

**All specifications and prices listed are subject to change without notice.*