

VALVCHEQ BACKFLOW PREVENTERS

ENCLOSURES

Enclosures for backflow prevention products



FEATURES

- Stainless steel for superior corrosion resistance.
- Available in single and double valve configurations.
- Hasp and staple locking mechanism to allow generic key padlocks.
- Generic keyed locking mechanism.
- Preformed to allow easy installation of 50mm waste to bottom of enclosure.
- Full stainless steel front panel or perspex window available.

GENERAL APPLICATION

For external or internal installations that require security and prevent vandalism.

TECHNICAL DATA

Suitable for valve sizes: DN 15 - 50


Wall recessed side entry.

Wall mounted bottom, rear and side entry.




SELECTION GUIDE

xamp	le: 015-	025 RP03	ENC	CA	DBL	RE
Valve s	ize					
15	25					
32	50					
Valve t	уре					
RP03						
DC03						
Enclos	ure					
Valve a	ssembly					
Comple	ete and assembled					
Valve o	onfiguration					
DBL	Double					
SGL	Single					
Inlet o	utlet configuration					
RE	Rear entry					
BE	Bottom entry					
SE	Side entry					
WR	Wall recessed					
WRPF	Wall recessed per	spex front				



Note: Wall mounted side entry single enclosure illustrated.



Note: Wall recessed double side entry single enclosure perspex front illustrated.